## WS 9220 KLIMASTAR

Design	
Material	
Seat / Backrest	PUR integral foam / PUR integral foam
Five star base xx20 Ø655mm	diecast aluminium
with dual castors (Ø 65mm)	unloaded braked - loaded unbraked
Column xx20	safety gas spring, chrome plated
Backrest bow	high-precision steel bar, Ø20 x 2,0mm
	2004 1015
Total height *	930 to 1215mm
Thickness of seat / backrest *	50mm / 50mm
Weight *	16.60kg
Landing consists	40010
Loading capacity	120kg
Adjustabilities	
Seat height (acc. DIN 68877) *	450 to 620mm
Seat tilt *	-8° to +1°
Seat lock	continuous
Backrest tilt *	-18° to +11°
	·
Details	
Backrest	
Width top / bottom *	325 / 400mm
Height *	450mm
· · - · <del>0</del> · · ·	1 2
Seat	
Width front / back *	470 / 415mm
Depth *	455mm

\*: production- or model-related differences are possible

Revision status 23.09.2019

We are constantly developing our products for you in design as well as in quality. Please contact us about your special requirements for work places and employees. We offer you individual solutions for special seat and standing work places.



**Characteristics** 

## WS 9220 KLIMASTAR



\*: The illustrated product may show accessories with surcharge.

