

## Model: UTS ERGO LINE

### Order number: 29-060967-003

Correct use: Passive storage



One-hand door technology (door handle). For the storage of flammable liquids. Type testing by MPA/TÜV SÜD according to DIN EN 14470-1, DIN EN 16121 and DIN EN 16122, EK5/AK4 09-10:2009 and AfPS GS 2019: 01 PAK Mark of approval: GS/CE mark, high quality mark of approval by TÜV SÜD Construction and colour:

- Outer carcass sheet steel, RAL 7035
- Doors sheet steel, RAL 1018
- Inner carcass of decor panels, RAL 7035 Fittings and features:
- Doors close automatically in case of fire
- Doors remain open in any position
- Cylinder lock for safe access
- Automatically extending pull-out tray sheet steel, RAL 7035
- Perforated sheet insert, RAL 7035
- Exhaust air connection socket at the rear of the cabinet
- Visual inspection of the ventilation opening
- Earthing connection at the rear of the cabinet
- Interior fittings conductively connected with carcass
- Classical slotted base, RAL 7015 Further technical information: [www.dueperthal.com](http://www.dueperthal.com)

Category:	Type 90 - flammable liquids
Model size	M
Outer width [mm]:	889
Outer depth [mm]:	594
Outer height [mm]:	631

Net weight [kg]:	149,00
Number of storage levels	1
Number of storage areas per storage level	1
Door operation	classical technology
Door technology	wing door technology