

Model: UTS ERGO LINE

Order number: 29-060667-001

Correct use: Passive storage



Classical door technology (door handle), door hung right. For the storage of flammable liquids. Type testing by MPA/TÜV SÜD according to DIN EN 14470-1, DIN EN 16121 and DIN EN 16122, EK5/AK4 09-10:2009 and AfPS GS 2019: 01 PAK Mark of approval: GS/CE mark, high quality mark of approval by TÜV SÜD Construction and colour:

- Outer carcass sheet steel, RAL 7035
- Door sheet steel, RAL 1018
- Inner carcass of decor panels, RAL 7035 Fittings and features:
- Door closes automatically in case of fire
- Door remains open in any position
- Cylinder lock for safe access
- Bottom tray sheet steel, RAL 7035
- Perforated sheet insert, RAL 7035
- Exhaust air connection socket at the rear of the cabinet
- Visual inspection of the ventilation opening
- Earthing connection at the rear of the cabinet
- Interior fittings conductively connected with carcass
- Classical slotted base, RAL 7015 Further technical information: www.dueperthal.com

Category:	Type 90 - flammable liquids
Model size	ST
Outer width [mm]:	601
Outer depth [mm]:	594

Outer height [mm]:	631
Net weight [kg]:	106,00
Number of storage levels	1
Number of storage areas per storage level	1
Door operation	classical technology
Door technology	wing door technology